

Tumble dryer

TD6-10



Dryer featuring exceptional savings and effortless use



Priority on people

Certified ergonomic design with a human-centered approach for an outstanding user experience

- Lint filter
The horizontal filter drawer is positioned for easy access and cleaning without the need to bend down
- Reversible door hanging for a convenient laundry flow
- Easy access to vital parts from front and rear for simple servicing



Long-term savings

Innovative features to save money and time, and embrace a sustainable lifestyle

- Moisture Balance (optional)
Helps to stop the drying process at the right time to save on energy costs



Pure control

Monitor your equipment and performance from anywhere, allowing to take action and to improve your business with OnE Laundry - the personal assistant for hygiene validation management, process management and revenue management (optional)



Outstanding productivity

Dry more laundry in less time: a game-changing improvement

- Reversing drum
Minimizes wrinkles and drying time to get an effective and even drying performance with 2 full loads per hour



Global Advanced Hygiene

Global Advanced Hygiene program package* with proven log 6 reduction** disinfection of textiles through the laundry process, fulfilling the criteria of all local approved standards

Main options and accessories

- Stainless steel base frame
- Connectable to booking-/payment system or coin meter
- Stainless steel drum, Stainless steel front



Images shown are a representation of the product only and variations may occur.

* Programs available in the standard library of all products, excluding products for specific segments where water temperature is not controllable.

** Log 6 reduction equals to 99,9999% viral infectivity reduction. The efficacy of reduction of SARS-CoV-2 and other pathogens in the process is confirmed by RISE (The Research Institute of Sweden) on the basis of Electrolux Professional laboratory data.

| Main specifications | | | TD6-10 | | | |
|-------------------------------------|------------|--|-----------------------|-----------|------------|------------|
| Rated capacity, filling factor 1:18 | kg/lb | | 10.6/23 | | | |
| filling factor 1:22 | kg/lb | | 8.6/19 | | | |
| Drum volume | litre | | 190 | | | |
| Drum diameter | mm | | 680 | | | |
| Heating, electric | kW | | 6.0/8.0 | | | |
| gas | BTU/h (kW) | | 20500/27300 (6.0/8.0) | | | |
| Consumption data* | | | EI 6.0 kW | EI 8.0 kW | Gas 6.0 kW | Gas 8.0 kW |
| Total time full load | min | | 35 | 27 | 36 | 29 |
| Energy consumption full load | kWh | | 3.45 | 3.53 | 3.67 | 3.74 |
| Evaporation | g/min | | 102 | 129 | 106 | 131 |
| Energy kWh/litre water evaporated | kWh/l | | 0.92 | 0.94 | - | - |

* At rated capacity 1:22, 100% cotton load at 50% initial moisture dried to 0%.

| Electrical connections | | | | | |
|------------------------|----------------------|-------|------------------|----------------|--------------------|
| Heating alternative | Main voltage | | Heating power kW | Total power kW | Recommended fuse A |
| | | Hz | | | |
| Electric heated | 220-240V 1/1N ~ | 50/60 | 6.0/8.0 | 6.4/8.4 | 35/50 |
| | 220-240V 3 ~ | 50/60 | 6.0/8.0 | 6.4/8.4 | 20/25 |
| | 380-415V 3N/3 ~ | 50/60 | 6.0/8.0 | 6.4/8.4 | 10/16 |
| | 440V 3 ~ | 60 | 6.0/8.0 | 6.4/8.4 | 10/16 |
| | 480V 3 ~ | 60 | 6.0/8.0 | 6.4/8.4 | 10/16 |
| | 115V 3 ~ | 60 | 4.1 | 4.5 | 25 |
| Gas heated | 220-480V 1/1N/3/3N ~ | 50/60 | * | 0.4 | 10 |

* Total power and recommended fuse does not depend on the heating power in those cases.

| Gas and air connections | | | TD6-10 |
|---------------------------------------|-----------------------|---------|-----------|
| Gas | ISO 7/1-R | | 1/2" |
| Gas pressure | Natural gas | Pa | 2000 |
| | | mbar | 20 |
| | Propane | Pa | 2800-5000 |
| | | mbar | 30 |
| Air outlet | | ø mm | 125 |
| Evacuated air | 6.0 kW | m³/h | 270 |
| | 8.0 kW | | 290 |
| Pressure drop | 6.0 kW | Max. Pa | 380 |
| | 8.0 kW | | 350 |
| Sound levels | | | |
| Sound power/pressure level at drying* | | | |
| | | dB(A) | 67/53 |
| Heat emission | | | |
| % of installed power, max | | | 15 |
| Shipping data** | | | |
| Weight | net, kg | | 99 |
| Shipping volume | m³ | | 0.83 |
| Dimensions in mm | | | |
| A | Width | | 720 |
| B(a) | Depth (Gas) | | 805 |
| B(b) | Depth (EI) | | 765 |
| B(c) | Depth | | 750 |
| C | Height | | 1115 |
| D | | | 405 |
| E | | | 45 |
| F | | | 180 |
| G | | | 90 |
| H | | | 115 |
| I | | | 80 |
| J | | | 560 |
| 1 | Operating panel | | |
| 2 | Door opening ø 400 mm | | |
| 3 | Electrical connection | | |
| 4 | Gas connection | | |
| 5 | Exhaust connection | | |

Front and side panes in silver grey and door handle in dark blue (color samples can be ordered on part number 472998313).

* Sound power levels measured according to ISO 60704.

** Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

